

JC952 U.S. PTO  
11/16/00

EXPRESS MAIL CERTIFICATE

Date 11/16/00 Label No. 2628224185US

I hereby certify that, on the date indicated above I deposited this paper or fee with the U.S. Postal Service & that it was addressed for delivery to the Assistant Commissioner for Patents, Washington, DC 20231 by "Express Mail Post Office to Addressee" service.

Name (Print)

Signature

DB Peck [Signature]

PLEASE CHARGE ANY DEFICIENCY UP TO \$300.00 OR CREDIT ANY EXCESS IN THE FEES DUE WITH THIS DOCUMENT TO OUR DEPOSIT ACCOUNT NO. 04-0100

JC571 U.S. PTO  
09/714798  
11/16/00

**DARBY & DARBY P.C.**

805 Third Avenue  
New York, New York 10022  
212-527-7700

Docket No: 6727/OH935

Box PATENT APPLICATION  
Assistant Commissioner for Patents  
Washington, DC 20231

Sir:

Enclosed please find an application for United States patent as identified below:

Inventor/s (name ALL inventors): Oren ROSENFELD


Title: **ELECTRONIC SHELF LABEL SYSTEMS AND METHODS**

including the items indicated:

1. Specification and 72 claims: 12 indep.; 60 dep.; 0 multiple dep.
2. ☐ Executed declaration and power of attorney  
☒ Unexecuted declaration and power of attorney
3. ☒ Formal drawings, 14 sheets (Figs. 1-4, 5A-5B, 6-14)  
☐ Informal drawings,    sheets (Figs. )

- [illegible]

Respectfully submitted,

  
S. Peter Ludwig  
Reg. No. 25,351  
Attorney for Applicant(s)

-2-

Docket No. 6727/0H935

PATENT FEE COMPUTATION SHEET

	No. of Claims Presented	Extra Claims Previously Paid For	Number of Extra Claims	Rate
Basic Fee . . . . .				\$710.00
Total Claims	72 - 20	- 0 = 52	x \$18.00	\$936.00
Independent Claims	12 - 3	- 0 = 9	x \$80.00	\$720.00
Multiple Dependent Claims		- if so, add	\$270.00	\$0.00
Surcharge for late submission of filing fee and/or declaration (\$130.00) . . . . .				\$0.00
SUBTOTAL . . . . .				\$0.00
<input type="checkbox"/> Small Entity REDUCTION (Half of Subtotal) . . . . .				\$0.00
Fee for recordation of assignment (\$40.00) . . . . .				\$0.00
Charge for filing non-English language application (\$130.00)				\$0.00
TOTAL . . . . .				\$2366.00

36681e16.at

12/11/00

#### FIELD OF THE INVENTION

The present invention relates to electronic shelf labels and to electronic shelf label systems generally.

#### BACKGROUND OF THE INVENTION

There are known in the prior art a variety of different types of electronic shelf labels and electronic shelf label systems. The following U.S. Patents and other publications are believed to represent the state of the art:

5,539,393; 5,553,412; 5,572,653; 5,753,900; 5,880,449; 5,933,813; 5,975,416; 6,031,585; 6,105,004.

JP 2000152857; DE 19840248; DE 19840251; EP 974918A2; AU 9923674; FR 2778775; FR 2772529; SE 9103048; RD 344094; GB 2249854.

WO 95/22798; WO 98/00819; WO 98/32115; WO 99/65288.

The disclosure in Section 3.7.4. of "Wireless Infrared Communications", by John R. Barry, Kluwer Academic Publishers, 1994, pp. 75 - 77 is believed to be relevant to part of the subject matter of the present invention.

The present applicant/assignee is the proprietor of the following published patents and patent applications: US Patent Nos. 5,880,449; 5,933,813; 6,105,004.

US Patent Application No. U.S.S.N. 09/147,422.

WO 98/00819; WO 96/32683;

#### EXPRESS MAIL CERTIFICATE

Date 4/16/00 Label No. 628224185 US

I hereby certify that, on the date indicated above I deposited this paper or fee with the U.S. Postal Service & that it was addressed for delivery to the Commissioner of Patents & Trademarks, Washington D.C. 20540 "Express Mail for Office to Addressee" service.

Name (Print) D. B. Peck

Signature [Signature]

# SUMMARY OF THE INVENTION

The present invention seeks to provide improved electronic shelf labels and electronic shelf labels systems.

There is thus provided in accordance with a preferred embodiment of the present invention an electronic shelf label including an LCD display, a housing including a protective at least partially transparent cover layer disposed over the LCD display and in spaced relationship thereto, and an at least partially transparent intermediate layer formed over the LCD display and substantially filling a space between the LCD display and the protective at least partially transparent cover layer.

Further in accordance with a preferred embodiment of the present invention the at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer and both of the LCD display and the protective at least partially transparent cover layer.

Still further in accordance with a preferred embodiment of the present invention the at least partially transparent intermediate layer is located with respect to the LCD display and to the protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.

Additionally in accordance with a preferred embodiment of the present invention, the electronic shelf label also includes at least one fuel cell powering the LCD display.

Preferably the fuel cell includes at least first and second printed circuit boards, each having electrical contacts formed thereon, the electrical contacts on the first and second

printed circuit boards each being in at least partial registration with each other, the printed circuit boards each being formed with a plurality of apertures generally surrounded by the electrical contacts, a plurality of electrodes, each electrode being located in one of the apertures, and a membrane disposed between the first and second printed circuit boards, the membrane providing electrical insulation between the electrical contacts on the first and second printed circuit boards and permitting ionic transfer thereacross between the electrodes, and the electrodes located in apertures on the first printed circuit board being exposed to a fuel, and the electrodes located in apertures on the second printed circuit board being exposed to air.

Moreover in accordance with a preferred embodiment of the present invention the fuel cell powering the LCD display includes a fuel tank, filling generally the volume of the housing not occupied by the display and the communicator.

Still further in accordance with a preferred embodiment of the present invention the index of refraction of the intermediate layer is identical to the index of refraction of at least one of the LCD display and the protective at least partially transparent cover layer.

Preferably the index of refraction varies from one surface of the intermediate layer to an opposite surface thereof.

There is also provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label system including a multiplicity of electronic shelf la-

bels, each including an IR transmitter for transmitting information relating to the electronic shelf label, at least one receiver receiving IR transmissions from the multiplicity of electronic shelf labels, the at least one receiver including an IR sensor, a non-IR visible light sensor, and circuitry for employing an output of the non-IR visible light sensor for reducing interference in a signal band sensed by the IR sensor.

Further in accordance with a preferred embodiment of the present invention there is provided an electronic shelf label system and wherein each of the multiplicity of electronic shelf labels includes an LCD display, a housing including a protective at least partially transparent cover layer disposed over the LCD display and in spaced relationship thereto, and an at least partially transparent intermediate layer formed over the LCD display and substantially filling a space between the LCD display and the protective at least partially transparent cover layer.

Preferably the at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer and both of the LCD display and the protective at least partially transparent cover layer.

Still further in accordance with a preferred embodiment of the present invention the at least partially transparent intermediate layer is located with respect to the LCD display and to the protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.

Moreover in accordance with a preferred embodiment of

the present invention each electronic shelf label also includes at least one fuel cell powering the LCD display.

Preferably the fuel cell includes at least first and second printed circuit boards, each having electrical contacts printed thereon, the electrical contacts on the first and second printed circuit boards being in at least partial registration with each other, the printed circuit boards each being formed with a plurality of apertures generally surrounded by the electrical contacts, a plurality of electrodes, each electrode being located in one of the apertures, and a membrane disposed between the first and second printed circuit boards, the membrane providing electrical insulation between the electrical contacts on the first and second printed circuit boards and permitting ionic transfer thereacross between the electrodes, and the electrodes being located in apertures on the first printed circuit board being exposed to a fuel, and the electrodes located in apertures on the second printed circuit board being exposed to air.

There is further provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label which includes a housing, an electrically driven display mounted in the housing, at least one electrically powered illuminator, at least one fuel cell powering the electrically driven display and the at least one electrically powered illuminator, and a data communicator providing display data to the electrically driven display from an external data source.

There is also provided in accordance with a preferred embodiment an electronic shelf label including a housing, an



electrically driven display mounted in the housing, at least one fuel cell powering the electrically driven display, the at least one fuel cell including a fuel tank, filling generally the volume of the housing not occupied by the display and the communicator, and a data communicator providing display data to the electrically driven display from an external data source.

Further in accordance with a preferred embodiment of the present invention there is provided an electronic shelf label which also includes at least one electrically powered illuminator, and wherein the at least one electrically powered illuminator and the electrically driven display have an average lifetime without requiring repowering of at least six months.

Still further in accordance with a preferred embodiment of the present invention the at least one fuel cell has an average mean power output of less than approximately 50 microwatts.

Additionally in accordance with a preferred embodiment of the present invention the at least one fuel cell has an average peak power output of less than approximately 3 milliwatt.

Moreover in accordance with a preferred embodiment of the present invention the fuel tank is fluid refuelable without requiring dismounting of the housing from a mounting location.

Furthermore in accordance with a preferred embodiment of the present invention the at least one fuel cell is replaceable without requiring dismounting of the housing from a mounting location.

There is also provided in accordance with yet a further embodiment of the present invention an electronic shelf label including a housing, an electrically driven display mounted in the housing, at least one electrically powered illuminator, at least one replaceable energy source powering the electrically driven display and the at least one electrically powered illuminator, and a data communicator providing display data to the electrically driven display from an external data source, the at least one replaceable energy source being replaceable without requiring dismounting of the housing from a mounting location.

Further in accordance with a preferred embodiment of the present invention the electronic shelf label also includes an at least partially transparent intermediate layer formed over the display and substantially filling a space between the display and the housing.

Still further in accordance with a preferred embodiment of the present invention the at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer and both of the LCD display and the housing.

Additionally in accordance with a preferred embodiment of the present invention at least partially transparent intermediate layer is located with respect to the display and the housing so as to substantially eliminate air gaps therebetween.

There is also provided in accordance with a preferred embodiment of the present invention a fuel cell including at least first and second printed circuit boards, each having elec-

trical contacts printed thereon, the electrical contacts on the printed circuit boards being in at least partial registration with each other, the printed circuit boards each being formed with a plurality of apertures generally surrounded by the electrical contacts, a plurality of electrodes, each electrode being located in one of the apertures, and a membrane disposed between the first and second printed circuit boards, the membrane providing electrical insulation between the electrical contacts on the first and second printed circuit boards and permitting ionic transfer thereacross between the electrodes, the electrodes being located in apertures on the first printed circuit board being exposed to a fuel, and the electrodes located in apertures on the second printed circuit board being exposed to air.

There is also provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label including a flexible electrically driven display mounted in the housing, at least one flexible power supply powering the electrically driven display, and a data communicator providing display data to said electrically driven display from an external data source.

There is further provided in accordance with a further embodiment of the present invention an electronic shelf label system including a multiplicity of flexible electronic shelf labels, each including an IR transmitter for transmitting information relating to the electronic shelf label, and at least one receiver receiving IR transmissions from the multiplicity of

flexible electronic shelf labels.

Further in accordance with a preferred embodiment of the present invention the at least one receiver includes an IR sensor, a non-IR visible light sensor, and circuitry for employing an output of the non-IR visible light sensor for reducing interference in a signal band sensed by the IR sensor.

Still further in accordance with a preferred embodiment of the present invention each of the multiplicity of electronic shelf labels comprises a flexible LCD display.

Additionally in accordance with a preferred embodiment of the present invention each electronic shelf label also includes at least one fuel cell powering the LCD display.

There is also provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label system including a multiplicity of electronic shelf labels, each including an electronic display for displaying product information, and a product information entry device which is operative to directly write product information to the electronic display when in propinquity thereto.

There is also provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label system including a multiplicity of electronic shelf labels, each including an IR receiver for receiving information relating to the electronic shelf label, and an electronic display for displaying product information based on the information received by the IR receiver, and at least one transmitter transmitting IR transmissions containing the information to the multiplicity of electronic shelf labels, the at least one transmitter being

characterized in that it transmits information including both price and product description.

Further in accordance with a preferred embodiment of the present invention the electronic display displays both the price and the product description.

Still further in accordance with a preferred embodiment of the present invention the receiver receives the information including both price and product description.

Additionally in accordance with a preferred embodiment of the present invention the electronic display includes a unitary LCD display.

Moreover in accordance with a preferred embodiment of the present invention the receiver receives the price information and the product information is supplied to the electronic display other than via the receiver.

Furthermore in accordance with a preferred embodiment of the present invention the electronic display includes at least two separate LCD displays, at least one of which is operative to display price information received via the receiver and at least one of which is operative to display product information received other than via the receiver.

Still further in accordance with a preferred embodiment of the present invention the electronic shelf label system also includes a portable product information entry device which is operative to supply product information to the electronic display when in propinquity thereto.

Preferably the portable product information entry

device is operative to receive a transmission from the transmitter including the product information and to provide the product information to the electronic display when in propinquity thereto.

Additionally in accordance with a preferred embodiment of the present invention the electronic shelf labels are flexible.

Moreover in accordance with a preferred embodiment of the present invention the portable product information entry device is operative to directly write product information onto the electronic display.

There is also provided in accordance with yet another preferred embodiment of the present invention a method of repowering an electronic shelf label including the following a housing, an electrically driven display mounted in the housing, at least one electrically powered illuminator, at least one replaceable energy source powering the electrically driven display and the at least one electrically powered illuminator, and a data communicator providing display data to the electrically driven display from an external data source, the method including the following step replacing the at least one replaceable energy source without requiring dismounting of the housing from a mounting location.

There is thus provided in accordance with yet another preferred embodiment of the present invention an electronic shelf label system including a multiplicity of electronic shelf labels, each electronic shelf label includes an RF receiver for receiving information relating to the electronic shelf label, and

an electronic display for displaying product information based on the information received by the RF receiver, and at least one transmitter transmitting RF transmissions containing the information to the multiplicity of electronic shelf labels, the at least one transmitter being characterized in that it transmits information including both price and product description.

Further in accordance with a preferred embodiment of the present invention the electronic display displays both the price and the product description.

Still further in accordance with a preferred embodiment of the present invention the receiver receives the information including both price and product description.

Additionally in accordance with a preferred embodiment of the present invention the electronic display comprises a unitary LCD display.

Moreover in accordance with a preferred embodiment of the present invention the receiver receives the price information and wherein the product information is supplied to the electronic display other than via the receiver.

Furthermore in accordance with a preferred embodiment of the present invention the electronic display includes at least two separate LCD displays, at least one of which is operative to display price information received via the receiver and at least one of which is operative to display product information received other than via the receiver.

Additionally in accordance with a preferred embodiment of the present invention the electronic shelf label system also

includes a portable product information entry device which is operative to supply product information to the electronic display when in propinquity thereto.

Preferably the portable product information entry device is operative to receive a transmission from the transmitter including the product information and to provide the product information to the electronic display when in propinquity thereto.

Furthermore in accordance with a preferred embodiment of the present invention the electronic shelf labels are flexible.

Still further in accordance with a preferred embodiment of the present invention the portable product information entry device is operative to directly write product information onto the electronic display.



## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description in which:

Fig. 1 is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 2 is a simplified exploded view pictorial illustration of a fuel cell constructed and operative in accordance with a preferred embodiment of the present invention;

Fig. 3 is a simplified partially cut-away illustration of the fuel cell of Fig. 2;

Fig. 4 is a simplified exploded view pictorial illustration of an electronic shelf label constructed and operative in accordance with a preferred embodiment of the present invention and including a fuel cell of the type illustrated in Figs. 2 & 3;

Figs. 5A & 5B are each a partially sectional, partially pictorial illustration of a fuel cell of the type shown in Figs. 2 & 3 coupled with a fuel tank in an arrangement such as that employed in the embodiment of Fig. 4;

Fig. 6 is a simplified pictorial illustration of an electronic shelf label constructed and operative in accordance with preferred embodiment of the present invention;

Fig. 7 is a simplified pictorial illustration of refueling the electronic shelf labels in accordance with one embodiment of the present invention;

Fig. 8 is a simplified pictorial illustration of replacing an energy source in the electronic shelf labels in accordance with one embodiment of the present invention;

Fig. 9 is a simplified diagrammatic illustration, taken along the line IX - IX in Fig. 8, which is useful in understanding the advantages of the structure of the embodiment of Fig. 8;

Fig. 10 is a simplified diagrammatic illustration of a receiver useful in the system of Fig. 1;

Fig. 11 is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with another preferred embodiment of the present invention;

Fig. 12 is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with still another preferred embodiment of the present invention;

Fig. 13 is a simplified pictorial view illustration of an electronic shelf label constructed and operative with a further preferred embodiment of the present invention; and

Fig. 14 is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with yet another preferred embodiment of the present invention which uses an RF data link.

## DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference is now made to Fig. 1, which is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with a preferred embodiment of the present invention. The system of Fig. 1 typically includes one or more servers 10 which may be located on the premises of a shop, such as a supermarket or alternatively may be located remotely therefrom and connected thereto by means of any suitable communication subsystem.

Located within the premises of the shop are one or more transceiver assemblies 12, which typically include a CPU 14, which is typically coupled to a plurality of LEDs 16 for optical information transmittal and to a plurality of optical sensors 18 for optical information receipt. Normally, the information transmittal and receipt is carried out using an infrared communication methodology.

A multiplicity of electronic shelf labels 20 are disposed throughout the shop, typically on shelf edges. In accordance with a preferred embodiment of the present invention, the electronic shelf labels 20 are each in wireless communication with one or more transceiver assemblies 12 for receiving and confirming information updates for display by the electronic shelf labels 20.

In accordance with a preferred embodiment of the present invention, each electronic shelf label 20 includes an LCD display 22 disposed in a housing 24 including a protective, at least partially transparent, cover layer 26 disposed over the LCD display 22 and in spaced relationship thereto. An at least par-

tially transparent intermediate layer 28 is preferably formed over the LCD display 22 and substantially fills the space between the LCD display 22 and the protective at least partially transparent cover layer 26.

The electronic shelf label 20 also comprises an IR emitter 29, such as a LED, for data transmission from the electronic shelf label 20 to an optical sensor 18 which is located in the transceiver 12. Additionally, the electronic shelf label 20 includes a photodiode 31 for receiving data transmissions from the LEDs 16, located in the transceiver 12.

Preferably, the at least partially transparent intermediate layer 28 has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer 28 and both LCD display 22 and the protective at least partially transparent cover layer 26.

In accordance with a preferred embodiment of the invention, the at least partially transparent intermediate layer 28 is located with respect to LCD display 22 and to the protective at least partially transparent cover layer 26 so as to substantially eliminate air gaps therebetween.

As seen in Fig. 1, and described hereinbelow in greater detail, the electronic shelf label 20 preferably includes at least one fuel cell 30 powering the LCD display 22 and preferably other elements of the electronic shelf label.

Additionally, as seen in Fig. 1, the electronic shelf label 20 preferably includes at least one electrically powered illuminator, which is powered by the fuel cell 30. The illumina-

tor may be a flashing LED 32. Alternatively or additionally, the illuminator may include a backlight (not shown) for LCD display 22. The backlight may include an electroluminescent element, an LED or any other suitable illumination element. It is also appreciated that the LCD display 22 may be replaced by any other suitable type of electrically powered display.

The fuel cell 30 preferably has an average mean power output of less than approximately 50 microwatts and an average peak power output of less than approximately 3 milliwatt. The fuel cell 30 is in fluid communication with a fuel tank 34. Fuel tank 34 preferably is fluid refuelable without requiring dismounting of the housing 24 from its mounting location. In accordance with one embodiment of the present invention, the at least one fuel cell is replaceable without requiring dismounting of the housing from its mounting location.

Preferably, the fuel tank 34 has sufficient energy storage capacity such that the electrically powered illuminator and the electrically driven display have an average lifetime without requiring repowering of at least six months.

Reference is now made to Fig. 2, which is a simplified exploded view pictorial illustration of a fuel cell, such as fuel cell 30 (Fig. 1), constructed and operative in accordance with a preferred embodiment of the present invention and to Fig. 3, which is a simplified partially cut-away illustration of the fuel cell of Fig. 2.

As seen in Figs. 2 & 3, the fuel cell typically includes first and second printed circuit boards 40 and 42, each having plated-through electrical contacts formed thereon. The

electrical contacts on circuit boards 40 and 42 are respectively designated by reference numerals 44 and 46. The electrical contacts 44 and 46 on respective first and second printed circuit boards 40 and 42 are preferably in partial registration with each other about respective apertures 48 and 50.

A plurality of electrodes 52 are located in respective apertures 48 and a plurality of electrodes 54 are located in respective apertures 50.

A membrane 56 is disposed between the first and second printed circuit boards 40 and 42, providing electrical insulation between the electrical contacts 44 and 46 on respective first and second printed circuit boards 40 and 42 and permitting ionic transfer thereacross between respective electrodes 52 and 54.

Electrodes 52 located in apertures 48 on the first printed circuit board 40 are exposed to a fuel, such as any suitable hydrocarbon fuel, and the electrodes 54 located in apertures 50 on the second printed circuit board 42 are exposed to air.

Reference is now made to Fig. 4, which is a simplified exploded view pictorial illustration of an electronic shelf label, such as electronic shelf label 20 (Fig. 1), constructed and operative in accordance with a preferred embodiment of the present invention and including a fuel cell of the type illustrated in Figs. 2 & 3 and to Figs. 5A & 5B are each a partially sectional, partially pictorial illustration of a fuel cell of the type shown in Figs. 2 & 3 coupled with a fuel tank in an arrangement such as that employed in the embodiment of Fig. 5B. It is

noted that Fig. 5A is cut along section line VA - VA shown in Fig. 4, while Fig. 5B is cut along section line VB - VB shown in Fig. 4. Reference is also made to Fig. 6.

As seen in Figs. 4, 5A, 5B and Fig. 6 and as described briefly above with reference to Fig. 1, the electronic shelf label 20 preferably comprises an LCD display 22, or any other suitable electrically driven display. The LCD display may be a conventional LCD display, preferably employed HTN technology, which is available from multiple vendors, such as Display Tech of Hong Kong and Yeboo of China.

The LCD display 22 is located in housing 24, typically including two parts which are typically snap-fit or press-fit together. Figs. 4, 5A & 5B illustrate respective front and rear housing portions 60 and 62. The front housing portion 60 preferably includes a protective, at least partially transparent, cover layer 26, which is disposed over the LCD display 22 and in spaced relationship thereto. An at least partially transparent intermediate layer 28, which is not seen in Figs. 5A and 5B, is preferably formed over the LCD display 22 and substantially fills the space between the LCD display 22 and the protective at least partially transparent cover layer 26.

Preferably, the at least partially transparent intermediate layer 28 has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer 28 and both LCD display 22 and the protective at least partially transparent cover layer 26.

In accordance with a preferred embodiment of the invention, the at least partially transparent intermediate layer 28 is

located with respect to LCD display 22 and to the protective at least partially transparent cover layer 26 so as to substantially eliminate air gaps therebetween.

An additional possible advantage of the provision of at least partially transparent intermediate layer 28 is the substantial elimination of the appearance of Newton rings or other types of Moire-type interference rings due to propinquity of the LCD display 22 and the cover layer 26.

As noted above with reference to Fig. 1, the electronic shelf label 20 preferably includes at least one fuel cell 30 powering the LCD display 22 and preferably other elements of the electronic shelf label. The fuel cell 30 is preferably constructed and operative as described hereinabove with reference to Figs. 2 and 3 and is preferably associated with fuel tank 34, which preferably fills most of the volume of the housing 24 which is not taken up by the remaining elements of the electronic shelf label, as seen clearly in Fig. 5B. Fuel tank 34 may be refueled via a fueling port 36 which communicates with the fuel tank 34 via a one-way valve 38.

Additionally, as also seen in Fig. 1, the electronic shelf label 20 preferably includes at least one electrically powered illuminator, which is powered by the fuel cell 30. In the illustrated embodiment, the illuminator is a flashing LED 32, which is mounted on the LCD display 22.

Referring additionally to Fig. 7, it is seen that the electronic shelf labels 20 constructed and operative in accordance with the illustrated embodiment of the present invention may



be refueled by hand, using a refueling tool 65, via a refueling port 36 formed in the front housing portion 60 and communicating with fuel tank 34 (as shown in Fig. 4). It is appreciated that such refueling may readily be accomplished without requiring removal of the electronic shelf label 20 from its mounting.

Reference is now made to Fig. 8, which is a simplified pictorial illustration of replacing an energy source in the electronic shelf labels in accordance with one embodiment of the present invention. As seen in Fig. 8, an energy source 70, which may be, for example, a battery or a fuel tank of a fuel cell, may be readily replaced in an electronic shelf label 72 without requiring detachment of the electronic shelf label 72 from its mounting location. The energy source 70 may be snap fit mountable in the electronic shelf label 72 or be removably and replaceably mounted therein in any other suitable manner.

Reference is now made to Fig. 9, which is a simplified diagrammatic illustration, taken along the line IX - IX in Fig. 6, and which is useful in understanding the advantages of the structure of the embodiment of Fig. 6. As seen in Fig. 9, the presence of the at least partially transparent intermediate layer 28 having an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer 28 and both LCD display 22 and the protective at least partially transparent cover layer 26 produces an enhanced display output intensity, indicated by solid arrow 39 as compared with an embodiment without layer 28 or having a layer 28 with a substantially non-optimal index of refraction, whose display output intensity is indicated by a

dashed arrow 40. The difference in amplitude and intensity between outputs 39 and 40 is accounted for by additional reflections at the boundary between the housing 24 and the intermediate layer 28 and between the LCD display 22 and the intermediate layer 28, as illustrated in Fig. 9.

It is appreciated that layer 28 preferably is selected to have an index of refraction which is identical to one or both of layers 22 and 26. Another preferred solution is that the index of refraction of layer 28 vary from an index of refraction identical to that of layer 22, adjacent layer 22 to an index of refraction identical to that of layer 26, adjacent layer 26. Alternatively the index of refraction of layer 28 may not be optimal but may nevertheless provide a result which is enhanced as compared with the absence of layer 28.

Reference is now made to Fig. 10, which is a simplified diagrammatic illustration of a preferred embodiment of a receiver 100 useful in the present invention, such as optical sensor 18 (Fig. 1) located within the transceiver 12 in the system of Fig. 1. As seen in Fig. 10, the receiver 100 preferably includes two processing channels, here designated by reference numerals 101 and 102. Both of the channels 101 and 102 receive radiation including both IR communication signals from electronic shelf labels 104 and possibly other IR communicators 106 as well as ambient radiation such as that from incandescent and fluorescent lamps 108. This ambient radiation includes both visible radiation and IR interference, which must be somehow separated from the IR communication signals.

Channel 101 includes an optical filter 110 which generally passes only radiation in the IR band, typically from 850 - 950 nm. The output of optical filter 110 is sensed by a photodiode 112, whose output is amplified by an amplifier 114 and passed through a low pass frequency filter 116 and supplied to an A/D converter 118.

Channel 102 includes a optical filter 120 which generally passes only radiation in the visible band, typically from 350 - 750 nm. The output of optical filter 120 is sensed by a photodiode 122, whose output is amplified by an amplifier 124 and passed through a low pass frequency filter 126 and supplied to an A/D converter 128.

The outputs of A/D converters 118 and 128 are preferably supplied to a digital signal processor (DSP) 130 or to any other suitable CPU. Preferred functionality of the DSP 130 to cancel the noise in the output of A/D converter 118 based on the output of A/D converter 128. This functionality is based on an appreciation that the electromagnetic interference in the visible band has certain similarities to that in the IR band.

Reference is now made to Fig. 11, which is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with another preferred embodiment of the present invention. As seen in Fig. 11, there is provided an electronic shelf label system comprising a multiplicity of electronic shelf labels 150 each including inter alia an IR receiver 152 for receiving information relating to the electronic shelf label 150 and an electronic display 154 for displaying price and product information based on the information

received by the IR receiver 152. The electronic display 154 is preferably a unitary LCD display.

The system also includes at least one transmitter 156, providing IR transmissions containing information to the multiplicity of electronic shelf labels 150. It is a particular feature of the present invention that the transmitter 156 transmits not only price information to labels 150. Preferably transmitter 156 transmits both price and product description information, which is preferably displayed concurrently on electronic display 154.

In accordance with an embodiment of the present invention, other information transmitted by transmitter 156 may also be displayed in additional display modes. This information may include, for example, stock information, shelf width information and other information which is normally not displayed to customers but may be displayed to aisle managers at suitable times or upon appropriate actuation by authorized personnel.

Reference is now made to Fig. 12, which is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with still another preferred embodiment of the present invention. The system of Fig. 12 may be similar to that of Fig. 11, and preferably includes a multiplicity of electronic shelf labels 170 each including inter alia an IR receiver 172 for receiving information relating to the electronic shelf label 170 and an electronic display 174 for displaying price and product information. In the system of Fig. 12, at least part of the information displayed on electronic

display 174 is supplied to the electronic shelf label 170 by a hand held unit 176.

The electronic display 174 is preferably a two-part LCD display including a first part 178 which displays information received by the IR receiver 172 and a second part 180 which displays information which is written therein by hand-held unit 176. Hand held unit 176 is preferably operative to directly write information onto second part 180 of electronic display 174. An example of a suitable hand-held unit 176 useful for this purpose is a model PT2000 Portable Terminal, commercially available from PSC INC. of Webster, New York, U.S.A., which is typically attached to a LCD writing device (not shown). The LCD writing device communicates with the hand-held unit 176 for replacing "old" product data from the LCD 180 with "new" product data. An example of a display 180 which is suitable for use with unit 176 is a bistable LCD. The hand-held unit 176 is typically operative when in propinquity or even in contact with the second part 180 of display 174. Alternatively direct writing of information onto second part 180 of electronic display 174 need not be carried out by a hand-held unit and need not take place at the shelf.

The system also includes at least one transmitter 182, transmitting IR transmissions containing the price information to the multiplicity of electronic shelf labels 170. It is a particular feature of the present invention that the hand held unit 176 and/or the transmitter 182 may transmit not only price information to labels 170.

Preferably both price and product description information is displayed concurrently on electronic display 174. In

accordance with an embodiment of the present invention, other information may also be displayed in additional display modes. This information may include, for example, stock information, shelf width information and other information which is normally not displayed to customers but may be displayed for aisle managers at suitable times or upon appropriate actuation by authorized personnel.

Reference is now made to Fig. 13, which is a simplified pictorial view illustration of an electronic shelf label constructed and operative with a further preferred embodiment of the present invention. As seen in Fig. 13, there is provided in accordance with a preferred embodiment of the present invention a flexible electronic shelf label 200, which is particularly useful and provides ease of mounting in conventional shelf edge mounts 202. The flexible electronic shelf label 200 preferably comprises a flexible plastic liquid crystal display 204 or other flexible electronic display, onto which are preferably mounted a transceiver 206, a power supply 208, such as a thin paper like battery commercially available from Power Paper Ltd. of Kibbutz Einat, Israel, or a fuel cell, and electronic control circuitry 210. The electronic shelf label 200 may operate in any suitable manner known in the art, inter alia in a manner shown and described hereinabove.

Reference is now made to Fig. 14 which is a simplified pictorial view illustration of an electronic shelf label system constructed and operative in accordance with yet another preferred embodiment of the present invention which uses an RF data

link.

The system of Fig. 14 typically includes one or more servers 310 which may be located on the premises of a shop, such as a supermarket or alternatively may be located remotely therefrom and connected thereto by means of any suitable communication subsystem.

Located within the premises of the shop are one or more RF transceiver assemblies 312. Information transmittal and receipt is carried out using RF communication methodology.

In accordance with a preferred embodiment of the present invention, transceiver assembly 312 includes at least one RF antenna 316.

A multiplicity of electronic shelf labels 320 are disposed throughout the shop, typically on shelf edges. In accordance with a preferred embodiment of the present invention, the electronic shelf labels 320 are each in wireless communication with one or more transceiver assemblies 312 for receiving and confirming information updates for display by the electronic shelf labels 320.

In accordance with a preferred embodiment of the present invention, each electronic shelf label 320 includes the LCD display 322 disposed in the housing 324 including the protective, at least partially transparent, cover layer 326 disposed over the LCD display 322 and in spaced relationship thereto. An at least partially transparent intermediate layer 28 is preferably formed over the LCD display 322 and substantially fills the space between the LCD display 322 and the protective at least partially transparent cover layer 326.

The electronic shelf label 320 also comprises an RF antenna 329 for data transmission and receiving from and to the electronic shelf label 320 to the antenna 316 which is located on the transceiver 312.

Preferably, the at least partially transparent intermediate layer 328 has an index of refraction which is selected so as to minimize reflection at interfaces between the at least partially transparent intermediate layer 328 and both LCD display 322 and the protective at least partially transparent cover layer 326.

In accordance with a preferred embodiment of the invention, the at least partially transparent intermediate layer 328 is located with respect to LCD display 322 and to the protective at least partially transparent cover layer 326 so as to substantially eliminate air gaps therebetween.

As seen in Fig. 14, the electronic shelf label 320 preferably includes at least one fuel cell 330 powering the LCD display 322 and preferably other elements of the electronic shelf label 320. The fuel cell 320 and its respective members are described hereinabove with respect to Figs. 2 and 3.

Additionally, as seen in Fig. 14, the electronic shelf label 320 preferably includes at least one electrically powered illuminator, which is powered by the fuel cell 330. The illuminator may be a flashing LED 332. Alternatively or additionally, the illuminator may include a backlight (not shown) for LCD display 322. The backlight may include an electroluminescent element, an LED or any other suitable illumination element. It is also appre-



ciated that the LCD display 322 may be replaced by any other suitable type of electrically powered display.

The fuel cell 330 preferably has an average mean power output of less than approximately 50 microwatts and an average peak power output of less than approximately 3 milliwatt. The fuel cell 330 is in fluid communication with a fuel tank 334. Fuel tank 334 preferably is fluid refuelable without requiring dismounting of the housing 334 from its mounting location. In accordance with one embodiment of the present invention, the at least one fuel cell is replaceable without requiring dismounting of the housing from its mounting location.

Preferably, the fuel tank 334 has sufficient energy storage capacity such that the electrically powered illuminator and the electrically driven display have an average lifetime without requiring repowering of at least six months.

It is appreciated that the embodiments described hereinabove with respect to Figs. 4 to 8 and 10 to 13, may also use an RF data link.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of the various features described hereinabove as well as variations and modifications which would occur to persons skilled in the art upon reading the specification and which are not in the prior art.

# CLAIMS

1. An electronic shelf label comprising:  
an LCD display;  
a housing including a protective at least partially transparent cover layer disposed over said LCD display and in spaced relationship thereto; and  
an at least partially transparent intermediate layer formed over said LCD display and substantially filling a space between said LCD display and said protective at least partially transparent cover layer.
2. An electronic shelf label according to claim 1 and wherein said at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between said at least partially transparent intermediate layer and both of said LCD display and said protective at least partially transparent cover layer.
3. An electronic shelf label according to claim 1 and wherein said at least partially transparent intermediate layer is located with respect to said LCD display and to said protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.
4. An electronic shelf label according to claim 2 and wherein said at least partially transparent intermediate layer is located with respect to said LCD display and to said protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.

5. An electronic shelf label according to claim 1 and also comprising at least one fuel cell powering said LCD display.

6. An electronic shelf label according to claim 5 and wherein said at least one fuel cell comprises:

at least first and second printed circuit boards, each having electrical contacts formed thereon, said electrical contacts on said first and second printed circuit boards being in at least partial registration with each other, said at least first and second printed circuit boards being formed with a plurality of apertures generally surrounded by said electrical contacts;

a plurality of electrodes, each electrode being located in one of said apertures; and

a membrane disposed between said first and second printed circuit boards, said membrane providing electrical insulation between said electrical contacts on said first and second printed circuit boards and permitting ionic transfer thereacross between said electrodes, and wherein

said electrodes located in apertures on said first printed circuit board being exposed to a fuel, and said electrodes located in apertures on said second printed circuit board being exposed to air.

7. An electronic shelf label according to claim 5 and wherein said fuel cell powering said LCD display includes a fuel tank, filling generally the volume of said housing not occupied by said display and said communicator.

8. An electronic shelf label according to claim 2 and

wherein said index of refraction is identical to the index of refraction of at least one of said LCD display and said protective at least partially transparent cover layer.

9. An electronic shelf label according to claim 2 and wherein said index of refraction varies from one surface of said intermediate layer to an opposite surface thereof.

10. An electronic shelf label system comprising:  
a multiplicity of electronic shelf labels, each including an IR transmitter for transmitting information relating to the electronic shelf label;

at least one receiver receiving IR transmissions from said multiplicity of electronic shelf labels, said at least one receiver including:

an IR sensor;

a non-IR visible light sensor; and

circuitry for employing an output of the non-IR visible light sensor for reducing interference in a signal band sensed by said IR sensor.

11. An electronic shelf label system according to claim 10 and wherein each of said multiplicity of electronic shelf labels comprises:

an LCD display;

a housing including a protective at least partially transparent cover layer disposed over said LCD display and in spaced relationship thereto; and

an at least partially transparent intermediate layer

formed over said LCD display and substantially filling a space between said LCD display and said protective at least partially transparent cover layer.

12. An electronic shelf label system according to claim 11 and wherein said at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between said at least partially transparent intermediate layer and both of said LCD display and said protective at least partially transparent cover layer.

13. An electronic shelf label system according to claim 11 and wherein said at least partially transparent intermediate layer is located with respect to said LCD display and to said protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.

14. An electronic shelf label system according to claim 12 and wherein said at least partially transparent intermediate layer is located with respect to said LCD display and to said protective at least partially transparent cover layer so as to substantially eliminate air gaps therebetween.

15. An electronic shelf label system according to claim 10 and wherein each electronic shelf label also comprises at least one fuel cell powering said LCD display.

16. An electronic shelf label system according to claim 15 and wherein said at least one fuel cell comprises:

at least first and second printed circuit boards, each

having electrical contacts printed thereon, said electrical contacts on said first and second printed circuit boards being in at least partial registration with each other, said at least first and second printed circuit boards being formed with a plurality of apertures generally surrounded by said electrical contacts;

a plurality of electrodes, each electrode being located in one of said apertures; and

a membrane disposed between said first and second printed circuit boards, said membrane providing electrical insulation between said electrical contacts on said first and second printed circuit boards and permitting ionic transfer thereacross between said electrodes, and wherein

said electrodes located in apertures on said first printed circuit board being exposed to a fuel, and said electrodes located in apertures on said second printed circuit board being exposed to air.

17. An electronic shelf label system according to claim 11 and wherein each electronic shelf label also comprises at least one fuel cell powering said LCD display.

18. An electronic shelf label system according to claim 17 and wherein said at least one fuel cell comprises:

at least first and second printed circuit boards, each having electrical contacts printed thereon, said electrical contacts on said first and second printed circuit boards being in at least partial registration with each other, said at least first and second printed circuit boards being formed with a

plurality of apertures generally surrounded by said electrical contacts;

a plurality of electrodes, each electrode being located in one of said apertures; and

a membrane disposed between said first and second printed circuit boards, said membrane providing electrical insulation between said electrical contacts on said first and second printed circuit boards and permitting ionic transfer thereacross between said electrodes, and wherein

said electrodes located in apertures on said first printed circuit board being exposed to a fuel, and said electrodes located in apertures on said second printed circuit board being exposed to air.

19. An electronic shelf label according to claim 15 and wherein said fuel cell powering said LCD display includes a fuel tank, filling generally the volume of said housing not occupied by said display and said communicator.

20. An electronic shelf label according to claim 17 and wherein said fuel cell powering said LCD display includes a fuel tank, filling generally the volume of said housing not occupied by said display and said communicator.

21. An electronic shelf label comprising:  
a housing;  
an electrically driven display mounted in said housing;  
at least one electrically powered illuminator;  
at least one fuel cell powering said electrically

driven display and said at least one electrically powered illuminator; and

a data communicator providing display data to said electrically driven display from an external data source.

22. An electronic shelf label according to claim 21 and wherein said at least one electrically powered illuminator and said electrically driven display have an average lifetime without requiring repowering of at least six months.

23. An electronic shelf label according to claim 21 and wherein said at least one fuel cell has an average mean power output of less than approximately 50 microwatts.

24. An electronic shelf label according to claim 21 and wherein said at least one fuel cell has an average peak power output of less than approximately 3 milliwatt.

25. An electronic shelf label according to claim 21 and wherein said fuel tank is fluid refuelable without requiring dismounting of said housing from a mounting location.

26. An electronic shelf label according to claim 21 and wherein at least fuel storage element of said at least one fuel cell is replaceable without requiring dismounting of said housing from a mounting location.

27. An electronic shelf label according to claim 21 and also comprising an at least partially transparent intermediate layer formed over said display and substantially filling a space



between said display and said housing.

28. An electronic shelf label according to claim 27 and wherein said at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between said at least partially transparent intermediate layer and both of said LCD display and said housing.

29. An electronic shelf label according to claim 27 and wherein said at least partially transparent intermediate layer is located with respect to said display and said housing so as to substantially eliminate air gaps therebetween.

30. An electronic shelf label according to claim 27 and wherein said index of refraction is identical to the index of refraction of at least one of said display and said housing.

31. An electronic shelf label comprising:  
a housing;  
an electrically driven display mounted in said housing;  
at least one fuel cell powering said electrically driven display, said at least one fuel cell including a fuel tank, filling generally the volume of said housing not occupied by said display and said communicator; and  
a data communicator providing display data to said electrically driven display from an external data source.

32. An electronic shelf label according to claim 31 and also comprising at least one electrically powered illuminator,

and wherein said at least one electrically powered illuminator and said electrically driven display have an average lifetime without requiring repowering of at least six months.

33. An electronic shelf label according to claim 31 and wherein said at least one fuel cell has an average mean power output of less than approximately 50 microwatts.

34. An electronic shelf label according to claim 31 and wherein said at least one fuel cell has an average peak power output of less than approximately 3 milliwatt.

35. An electronic shelf label according to claim 31 and wherein said fuel tank is fluid refuelable without requiring dismounting of said housing from a mounting location.

36. An electronic shelf label according to claim 31 and wherein at least fuel storage element of said at least one fuel cell is replaceable without requiring dismounting of said housing from a mounting location.

37. An electronic shelf label comprising:  
a housing;  
an electrically driven display mounted in said housing;  
at least one electrically powered illuminator;  
at least one replaceable energy source powering said electrically driven display and said at least one electrically powered illuminator; and

a data communicator providing display data to said electrically driven display from an external data source, said at

least one replaceable energy source being replaceable without requiring dismounting of said housing from a mounting location.

38. An electronic shelf label according to claim 37 and also comprising an at least partially transparent intermediate layer formed over said display and substantially filling a space between said display and said housing.

39. An electronic shelf label according to claim 38 and wherein said at least partially transparent intermediate layer has an index of refraction which is selected so as to minimize reflection at interfaces between said at least partially transparent intermediate layer and both of said LCD display and said housing.

40. An electronic shelf label according to claim 38 and wherein said at least partially transparent intermediate layer is located with respect to said display and said housing so as to substantially eliminate air gaps therebetween.

41. A fuel cell comprising:

at least first and second printed circuit boards, each having electrical contacts printed thereon, said electrical contacts on said first and second printed circuit boards being in at least partial registration with each other, said at least first and second printed circuit boards being formed with a plurality of apertures generally surrounded by said electrical contacts;

a plurality of electrodes, each electrode being located in one of said apertures; and

a membrane disposed between said first and second printed circuit boards, said membrane providing electrical insulation between said electrical contacts on said first and second printed circuit boards and permitting ionic transfer thereacross between said electrodes, and wherein

said electrodes located in apertures on said first printed circuit board being exposed to a fuel, and said electrodes located in apertures on said second printed circuit board being exposed to air.

42. An electronic shelf label comprising:  
a flexible electrically driven display;  
at least one flexible power supply powering said electrically driven display; and  
a data communicator providing display data to said electrically driven display from an external data source.

43. An electronic shelf label system comprising:  
a multiplicity of flexible electronic shelf labels, each including an IR transmitter for transmitting information relating to the electronic shelf label; and  
at least one receiver receiving IR transmissions from said multiplicity of flexible electronic shelf labels.

44. An electronic shelf label system according to claim 43 and wherein said at least one receiver includes:

an IR sensor;  
a non-IR visible light sensor; and  
circuitry for employing an output of the non-IR visible

light sensor for reducing interference in a signal band sensed by said IR sensor.

45. An electronic shelf label system according to claim 44 and wherein each of said multiplicity of electronic shelf labels comprises a flexible LCD display.

46. An electronic shelf label system according to claim 45 and wherein each electronic shelf label also comprises at least one fuel cell powering said LCD display.

47. An electronic shelf label system according to claim 46 and wherein said at least one fuel cell comprises:

at least first and second printed circuit boards, each having electrical contacts printed thereon, said electrical contacts on said first and second printed circuit boards being in at least partial registration with each other, said at least first and second printed circuit boards being formed with a plurality of apertures generally surrounded by said electrical contacts;

a plurality of electrodes, each electrode being located in one of said apertures; and

a membrane disposed between said first and second printed circuit boards, said membrane providing electrical insulation between said electrical contacts on said first and second printed circuit boards and permitting ionic transfer thereacross between said electrodes, and wherein

said electrodes located in apertures on said first printed circuit board being exposed to a fuel, and said elec-

trodes located in apertures on said second printed circuit board being exposed to air.

48. An electronic shelf label according to claim 46 and wherein said fuel cell powering said LCD display includes a fuel tank.

49. An electronic shelf label according to claim 46 and wherein said at least one fuel cell has an average peak power output of less than approximately 3 milliwatt.

50. An electronic shelf label according to claim 46 and wherein said one fuel tank is fluid refuelable without requiring dismounting of said housing from a mounting location.

51. An electronic shelf label system comprising:  
a multiplicity of electronic shelf labels, each including an electronic display for displaying product information; and  
a product information entry device which is operative to directly write product information to said electronic display when in propinquity thereto.

52. An electronic shelf label system comprising:  
a multiplicity of electronic shelf labels, each including:

an IR receiver for receiving information relating to the electronic shelf label; and

an electronic display for displaying product information based on said information received by said IR receiver; and

at least one transmitter transmitting IR transmissions containing said information to said multiplicity of electronic shelf labels,

said at least one transmitter being characterized in that it transmits information including both price and product description.

53. An electronic shelf label system according to claim 52 and wherein said electronic display displays both said price and said product description.

54. An electronic shelf label system according to claim 53 and wherein said receiver receives said information including both price and product description.

55. An electronic shelf label system according to claim 53 and wherein said electronic display comprises a unitary LCD display.

56. An electronic shelf label system according to claim 53 and wherein said receiver receives said price information and wherein said product information is supplied to said electronic display other than via said receiver.

57. An electronic shelf label system according to claim 53 and wherein said electronic display comprises at least two separate LCD displays, at least one of which is operative to display price information received via said receiver and at least one of which is operative to display product information received other than via said receiver.

58. An electronic shelf label system according to claim 55 and also comprising a portable product information entry device which is operative to supply product information to said electronic display when in propinquity thereto.

59. An electronic shelf label system according to claim 58 and wherein said portable product information entry device is operative to receive a transmission from said transmitter including said product information and to provide said product information to said electronic display when in propinquity thereto.

60. An electronic shelf label according to claim 52 and wherein said electronic shelf labels are flexible.

61. An electronic shelf label system according to claim 58 and wherein said portable product information entry device is operative to directly write product information onto said electronic display.

62. A method of repowering an electronic shelf label including:

a housing;

an electrically driven display mounted in said housing;

at least one replaceable energy source powering said electrically driven display; and

a data communicator providing display data to said electrically driven display from an external data source,

the method comprising:

replacing said at least one replaceable



energy source without requiring dismounting of said housing from a mounting location.

63. An electronic shelf label system comprising:  
a multiplicity of electronic shelf labels, each including:

an RF receiver for receiving information relating to the electronic shelf label; and

an electronic display for displaying product information based on said information received by said RF receiver; and

at least one transmitter transmitting RF transmissions containing said information to said multiplicity of electronic shelf labels,

said at least one transmitter being characterized in that it transmits information including both price and product description.

64. An electronic shelf label system according to claim 63 and wherein said electronic display displays both said price and said product description.

65. An electronic shelf label system according to claim 64 and wherein said receiver receives said information including both price and product description.

66. An electronic shelf label system according to claim 64 and wherein said electronic display comprises a unitary LCD display.

67. An electronic shelf label system according to claim 64 and wherein said receiver receives said price information and wherein said product information is supplied to said electronic display other than via said receiver.

68. An electronic shelf label system according to claim 64 and wherein said electronic display comprises at least two separate LCD displays, at least one of which is operative to display price information received via said receiver and at least one of which is operative to display product information received other than via said receiver.

69. An electronic shelf label system according to claim 66 and also comprising a portable product information entry device which is operative to supply product information to said electronic display when in propinquity thereto.

70. An electronic shelf label system according to claim 69 and wherein said portable product information entry device is operative to receive a transmission from said transmitter including said product information and to provide said product information to said electronic display when in propinquity thereto.

71. An electronic shelf label according to claim 63 and wherein said electronic shelf labels are flexible.

72. An electronic shelf label system according to claim 69 and wherein said portable product information entry device is operative to directly write product information onto said electronic display.

# ABSTRACT OF THE DISCLOSURE

This invention discloses an electronic shelf label including an LCD display, a housing including a protective at least partially transparent cover layer disposed over the LCD display and in spaced relationship thereto, and an at least partially transparent intermediate layer formed over the LCD display and substantially filling a space between the LCD display and the protective at least partially transparent cover layer.

1. An electronic shelf label comprising:  
an LCD display;  
a housing including a protective at least partially transparent cover layer disposed over the LCD display and in spaced relationship thereto;  
an at least partially transparent intermediate layer formed over the LCD display and substantially filling a space between the LCD display and the protective at least partially transparent cover layer.

FIG. 1 is a perspective view of a computer system 10, including a CPU 14, a memory 16, and a display 18, connected to a network 20. The system 10 is shown in a perspective view, with the CPU 14, memory 16, and display 18 connected to a network 20. The network 20 is shown in a perspective view, with the CPU 14, memory 16, and display 18 connected to it. The network 20 is shown in a perspective view, with the CPU 14, memory 16, and display 18 connected to it.

FIG. 1





FIG. 2 is a perspective view of the device 100, showing the top surface 40 and the bottom surface 42. The top surface 40 includes a plurality of openings 44, 46, 48, and 50. The bottom surface 42 includes a plurality of openings 44, 46, 48, and 50. The device 100 is shown in a perspective view, with the top surface 40 and the bottom surface 42 being visible. The openings 44, 46, 48, and 50 are arranged in a grid pattern on both surfaces. The device 100 is shown in a perspective view, with the top surface 40 and the bottom surface 42 being visible. The openings 44, 46, 48, and 50 are arranged in a grid pattern on both surfaces.

FIG. 2








FIG. 5A




FIG. 5B






FIG. 6




FIG. 7 is a perspective view of the device 10 in use in a grocery store aisle. A person is shown using the device 10 to scan a product on a shelf. The device 10 is a handheld unit with a display screen 20 and a scanner 36. The scanner 36 is used to scan a product 65 on a shelf 60. The device 10 is shown in a perspective view, and the person is shown in profile. The device 10 is a handheld unit with a display screen 20 and a scanner 36. The scanner 36 is used to scan a product 65 on a shelf 60. The device 10 is shown in a perspective view, and the person is shown in profile.




FIG. 7




FIG. 8 is a perspective view of a person using the device 70 to select a product from a shelf 72.




FIG. 8

FIG. 9





FIG. 10








FIG. 13 is a perspective view of a person using the device 200 to scan a product 210 from a shelf 202. The device 200 is a handheld unit with a display 204 and a camera 206. The person is holding the device 200 and pointing it at the product 210. The shelf 202 contains various products, including bottles and boxes. An inset shows a close-up of the device 200 scanning the product 210, with the display 204 showing a barcode and the camera 206 capturing the product.





FIG. 13



FIG. 14



**DECLARATION  
AND POWER OF ATTORNEY  
Original Application**

As a below named inventor, I declare that the information given herein is true, that I believe that I am the original, first and sole inventor if only one name is listed at 1 below, or a joint inventor if plural inventors are named below, of the invention entitled:

**ELECTRONIC SHELF LABEL SYSTEMS AND METHODS**

which is described and claimed in:

☒ the attached specification or ☐ the specification in application  
Serial No. , filed  
(for declaration not accompanying appl.)

that I do not know and do not believe that the same was ever known or used in the United States of America before my or our invention thereof or patented or described in any printed publication in any country before my or our invention thereof, or more than one year prior to this application, or in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to patentability in accordance with 37 CFR §1.56. I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I hereby claim the priority benefits under 35 U.S.C. §119 of any application(s) for patent or inventor's certificate listed below. All foreign applications for patent or inventor's certificate on this invention filed by me or my legal representatives or assigns prior to the application(s) of which priority is claimed are also identified below.

**PRIOR APPLICATION(S), IF ANY, OF WHICH PRIORITY IS CLAIMED**

<u>COUNTRY</u>	<u>APPLICATION NO.</u>	<u>DATE OF FILING</u>
<b>NONE</b>		

**ALL FOREIGN APPLICATIONS, IF ANY, FILED PRIOR  
TO THE APPLICATION(S) OF WHICH PRIORITY IS CLAIMED**

COUNTRY                      APPLICATION NO.                      DATE OF FILING

**POWER OF ATTORNEY:**

As a named inventor, I hereby appoint the following attorney(s) and/or agents(s) to prosecute this application and transact all business in the Patent and Trademark office connected therewith: Gordon D. Coplein #19,165, William F. Dudine, Jr. #20,569, Michael J. Sweedler #19,937, S. Peter Ludwig #25,351, Paul Fields #20,298, Marc S. Gross #19,614, Joseph B. Lerch #26,936, Melvin C. Garner #26,272, Ethan Horwitz #27,646, Beverly B. Goodwin #28,417, Adda C. Gogoris #29,714, Martin E. Goldstein #20,869, Bert J. Lewen #19,407, Henry Sternberg #22,408, Peter C. Schechter #31,662, Robert Schaffer #31,194, Robert C. Sullivan, Jr. #30,499, Ira J. Levy #35,587, Joseph R. Robinson #33,448, Scott G. Lindvall #40,325

all of the firm of DARBY & DARBY P.C., 805 Third Avenue, New York, NY 10022

SEND CORRESPONDENCE TO:

DIRECT TELEPHONE CALLS TO:

DARBY & DARBY P.C.  
805 Third Avenue  
New York, NY 10022

S. Peter Ludwig  
  
212-527-7700

**FULL NAME AND RESIDENCE OF INVENTOR 1**

LAST NAME: ROSENFELD                      FIRST NAME: Oren                      MIDDLE NAME:  
CITY: Mazkeret-Batya                      STATE OR FOREIGN COUNTRY: Israel                      COUNTRY OF CITIZENSHIP: Israel

POST OFFICE ADDRESS: 9 Eshel Street                      CITY: Mazkeret-Batya                      STATE OR COUNTRY: Israel                      ZIP CODE: 76804

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 1: \_\_\_\_\_ DATED: \_\_\_\_\_  
Oren ROSENFELD